

2. (Twice Amended) A method of processing signals at a receiver station based on at least one information transmission, the method comprising the steps of:

- SUB F1  
E1
- (a) receiving some information content and a first control signal in said at least one information transmission, said information content describing at least one of a product and a service;
  - (b) generating a benefit datum by processing subscriber data in response to said first control signal;
  - (c) delivering said information content and said benefit datum at an output device at said receiver station;
  - (d) inputting a subscriber reaction to at least one of said delivered information content and said delivered benefit datum;
  - (e) generating a second control signal that controls said receiver station based on said inputted subscriber reaction; and
  - (f) controlling said receiver station based on said inputted subscriber reaction.

3. (Unchanged) The method of claim 2, further comprising the step of storing said subscriber datum at a computer at said receiver station, said subscriber datum being an investment datum.

4. (Unchanged) The method of claim 2, further comprising the step of programming said computer to respond to said control signal.

SUB F3  
E2  
cont

5. (Twice Amended) A method of communicating subscriber specific data of a subscriber from a subscriber station of said subscriber to at least one remote station, said method comprising the steps of:

- (1) storing subscriber data of said subscriber at said subscriber station;

- 5213  
B3
- E2  
concl
- (2) receiving at said subscriber station at least one instruct signal which is effective to generate a control signal based on a subscriber reaction of said subscriber to at least one of a recommendation and an offer, each of said at least one of said recommendation and said offer including a receiver specific benefit datum;
  - (3) generating, under direction of instructions of said at least one instruct signal, at said subscriber station, said subscriber specific data;
  - (4) receiving said subscriber reaction to said at least one of said recommendation and said offer at said subscriber station;
  - (5) transferring said subscriber specific data from said subscriber station to said at least one remote station based on said step of receiving said subscriber reaction.
- 

Please cancel claims 6 to 8.

5213  
F4

E3  
const

9. (Twice Amended) A method of controlling at least one of a plurality of receiver stations each of which includes one of a broadcast receiver and a cablecast receiver, at least one processor, a signal detector, said signal detector adapted to detect signals within one of a broadcast transmission and a cablecast transmission, and said at least one processor programmed to respond to said signals, said method of controlling comprising the steps of:

- (1) receiving at one of a broadcast transmitter station and a cablecast transmitter station an instruct signal which is effective at said at least one of said plurality of receiver stations to generate a first control signal based on a subscriber reaction to at least one of a recommendation and an offer, each of said at least one of said recommendation and said offer including a receiver specific benefit datum;
- (2) transferring said instruct signal from said transmitter station to a transmitter;

SUB  
F4  
E3  
could

(3) receiving at least one second control signal at said transmitter station, said second control signal addressing said instruct signal to said processor of said at least one of said plurality of receiver stations; and

(4) transferring said at least one second control signal from said transmitter station to said transmitter, said transmitter station doing one of broadcasting and cablecasting said instruct signal and said at least one second control signal to said at least one of said plurality of receiver stations.

---

10. (Unchanged) The method of claim 9, wherein at least one of said instruct signal and said second control signal is embedded in the non-visible portion of a television signal.

---

SUB  
F4  
E4

11. **(Twice Amended)** The method of claim 9, wherein said at least one second control signal identifies at least two of said plurality of receiver stations asynchronously and each of said at least two receiver stations receive and respond to said instruct signal asynchronously.

12. **(Twice Amended)** The method of claim 9, wherein a switch communicates signals selectively between a transmitter station receiver and at least one of a memory and a recorder, and said transmitter, said method further comprising detecting a third control signal which is effective at the transmitter station to cause communication.

---

13. (Unchanged) The method of claim 9, wherein a controller controls a switch to communicate to said transmitter a selected signal, further comprising detecting a third control signal which is effective at the transmitter station to cause transmission.

14. (Unchanged) The method of claim 9, further comprising transmitting to a receiver station at least one datum that designates a time of transmission of said instruct signal.

**Please cancel claim 15.**

Sub  
P8  
E5

16. (Twice Amended) The method of claim 9, wherein said at least one of said plurality of receiver stations at least one of detects the presence of said at least one second control signal and responds to said instruct signal on the basis of a signal location in an information transmission, said method further comprising the step of causing at least some of at least one of said at least one second control signal and said instruct signal to be transmitted in said location.

**Please cancel claim 17.**

Sub  
FR  
E6  
Cont

18. (Twice Amended) A method of processing signals at a receiver station based on one of at least one broadcast transmission and at least one cablecast transmission, the method comprising the steps of:

- (a) receiving a first control signal and at least one of video and audio in said transmission;
- (b) generating information by processing subscriber data in response to said first control signal;
- (c) delivering said at least one of video and audio at an output device at said receiver station;
- (d) inputting a subscriber response to said delivered at least one of video and audio;

- SUB  
R  
E6  
Cmld
- (e) generating a second control signal based on said inputted subscriber response and said generated information; and
- (f) controlling said receiver station in accordance with said second control signal.
- 

SUB  
R  
E7

19. **(Amended)** The method of claim 5, wherein each of said at least one of said recommendation and said offer is transmitted from a transmitter to said subscriber station and is specific to said transmitter.

---

20. **(Amended)** The method of claim 5, wherein each of said at least one of said recommendation and said offer is transmitted to said subscriber station in one of a broadcast transmission and a cablecast transmission and is specific to said one of said broadcast transmission and said cablecast transmission.

---

21. **(Unchanged)** A method of delivering a receiver specific recommendation at a video receiver station including:

receiving at least one information transmission at said video receiver station, said information transmission including generally applicable information and a plurality of recommendation control signals, said generally applicable information including (1) some of said receiver specific recommendation and (2) video to serve as a basis on which to present said some of said receiver specific recommendation, at least said plurality of recommendation control signals being received from at least one remote transmitter station;

storing at least some of said generally applicable information and said plurality of recommendation control signals at said video receiver station;

outputting said video at a video monitor;